

ALLIED PRESSROOM CHEMISTRY MATERIAL SAFETY DATA SHEET

	S	SECTIO)N 1 F	PRO	DUCT	IDENTIFIC	ATION		JSE		
PRODUCT IDENTIFIER : ALLIED REJUVENATE (Cleaner for Printing Blankets and Rollers)									0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe HEALTH HAZARD: 2		
MANUFACTURER'S NAME: ALLIED PRESSROOM CHEMISTRY.									FIRE HAZAF REACTIVITY PROTECTIV		
STREET ADDRESS 2040 LEE STREET, HOLLYWOOD, FLORIDA, 33020, USA											
OFFICE TELEPHONE: FAX: 800-327-8487 954-5			FAX: 954-923-6462			24 HR. EMERGENCY TELEPHONE 800-424-9300 CHEMTREC		Saf Glas	242	Protective Bloves Apron	
THIS IS AN INDUSTRIAL PRODUCTS POSE AN IN COMPLETE LABEL AND	HERE	NT HEAL	TH RIS	K. BE	FORE U	ISE ALWAYS R			BREATHE VA	APORS. DO NOT GET IN EYES, N CLOTHING. DO NOT INGEST	
		SEC	CTION	N 2 -	- INGR	REDIENT IN	FORM	ATION			
INGREDIENTS *These ingredients are subject to the rep requirements of SARA 313 and 40 CFI	*These ingredients are subject to the reporting		% CA		NUMBER	JMBER HAZAF					
Aliphatic Naphtha			20 – 40 80		0-30-6	ACGIH (TWA-TLV) –100 p		00 ppm			
Acetone	Acetone		15 67		-64-1	ACGIH (TLV	GIH (TLV) TWA 500 ppr				
Isopropyl alcohol	Isopropyl alcohol) - 20 6		-63-0	ACGIH (TLV) TWA 4	00 ppm			
2-Butoxyethanol *		20 - 40		111-76-2		ACGIH (TLV) TWA 25		25 ppm			
Ethyl Acetate					-78-6		ACGIH (TLV) TWA 400 pp				
ALL INGREDIENTS ARE LISTED IN THE US TOXIC SUBSTANCE CONTROL ACT (TSCA)											
			SE	CTI	ON 3 -	PHYSICAL	DATA				
PHYSICAL STATE LIQUID	ODOR AND APPEAR Clear colorless liquid, Hydrocarbon/alcohol				WATER S	SOLUBILITY	DLUBILITY PH Not app			SPECIFIC GRAVITY 0.82	
VAPOR PRESSURE (MM Hg) 185 @ 20°C	/I Hg) (AIR=1)		EVAPORA (Butyl ace <1					NG POINT 340	(°F)	V.O.C.'s less exempt pds 6.18 lb per Gallon 741 g/liter	
		SEC	TION	4 -	FIRE		OSION	DATA			
FLAMMABILITY YES ■ NO □		SECTION 4 - FIRE AND EXPLOSION DATA IF YES, UNDER WHICH CONDITIONS? * Heat, sparks and open flame.									
EXTINGUISHING MEDIA CARBON DIOXIDE, DRY CHEMICAL, UNIVE				AL FC	DAM.		SPECIAL FIRE FIGHTING PROCEDURES: Use self contained breathing apparatus.				
FLASHPOINT (°F) AND METHOD < 4 F by TCC			UPPER FLAMM (% BY VOLUM			MMABLE LIMI ⁻ JME) : Unknowi					
				HAZARDOUS COMBUSTION PRODUCTS Oxides of carbon and hydrocarbons.							
EXPLOSION DATA * NOT KNOWN			SENSITIVITY TO IMPACT - NO			SENSITIV YES	SENSITIVITY TO STATIC DISCHARGE YES			E	
			SEC	CTIC)N 5 - I	REACTIVIT	Y DAT	A			
CHEMICAL STABILITY CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION YES NO □ None □											
INCOMPATIBILTY WITH OTHER SUBSTANCES Strong oxidizing agents, strong reducing agents											
HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide and hydrocarbons							nis produc	t is non - pl	hotochemically reactive		



PREPA

PRODUCT IDENTIFIER * ALLIED REJUVENATE

SKIN CONTACT

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY

SKIN ABSORPTION

N ■ EYE CONTACT ■

INHALATION

INGESTION

ACUTE EXPOSURE TO PRODUCT: Inhalation - Inhalation can cause severe irritation of the respiratory tract, signs of central nervous system depression, dizziness nausea and headache. Eye - Will cause severe irritation, burning, redness and tearing. Skin - Can cause irritation, redness burning and drying. Ingestion causes irritation of the digestive tract. Aspiration into the lungs can lead to pulmonary odema and chemical pneumonia which can prove fatal. Prolonged over-exposure can lead to narcosis, respiratory failure, coma.

CHRONIC EXPOSURE TO PRODUCT: Prolonged skin contact may aggravate an existing dermatitis. Prolonged and repeated exposure to the pure solvent contained in this product has been reported to cause permanent brain and central nervous system damage.

CARCINOGENICITY: No ingredient in excess of 0.1% listed as carcinogenic by IARC, NTP, OSHA

TARGET ORGAN EFFECTS: Eyes, skin irritation

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with running water for at least 15 minutes. Seek medical attention.

SKIN: wash affected area with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical attention.

INGESTION: Do not induce vomiting. Material is an aspiration hazard, may enter lungs and cause lung damage. Seek immediate medical attention.

SECTION 7 - PREVENTATIVE MEASURES

GLOVES	RESPIRATOR: Use NIOSH approved SCBA in	EYE (SPECIFY)					
Nitrile for incidental, non-immersion contact.	emergency situations or confined areas.	Splash proof goggles or face shield					
CLOTHING : Boots, aprons, or chemical suits should be used when necessary to prevent skin contact.							
ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) : Use local exhaust or dilution ventilation as appropriate to control exposure below permissible levels. Vapors are heavier than air and will collect in low areas							
LEAK AND SPILL PROCEDURE : Extinguish all sources of ignition. Provide maximum ventilation. Dike area to contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.							
WASTE DISPOSAL : Contaminated vermiculite or porous surface must be disposed of in a permitted hazardous waste facility. Recovered liquids may be reprocessed or incinerated in a permitted hazardous waste facility. In all cases material should be disposed of in accordance with all applicable regulations.							
HANDLING PROCEDURES AND EQUIPMENT : Keep container closed when not in use. Store only in closed, properly labeled containers. Store as VERY FLAMMABLE LIQUID. Store in a cool, dry, well ventilated area away from heat sparks and open flames. Treat empty containers as containing hazardous residues.							
ADDITIONAL INFORMATION							
CALIFORNIA PROPOSITION 65 : This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness. This product contains the following chemicals known by the state of California to cause cancer : benzene, ethylene oxide. This product contains following chemicals known by the state of California to cause reproductive harm : benzene, ethylene oxide							

SHIPPING INFORMATION: Flammable liquids, NOS (acetone, ethyl acetate), 3, UN 1993, PG II

SECTION 9 - PREPARATION AND DATE OF MSDS								
RED BY (GROUP DEPARTMENT, ETC.) PRESSROOM CHEMISTRY TECHNICAL SERVICES DEPARTMENT	PHONE NUMBER 1-800-327-8487	DATE April 2010						
FRESSROOM CHEMISTRY TECHNICAL SERVICES DEFARIMENT	1-800-327-8487	April 2010						

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that hereof.