

ALLIED PRESSROOM CHEMISTRY

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT IDENTIFICATION							AND USE		
PRODUCT IDENTIFIER: ALLIED SLIP (Lubricant for printing presses)							0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe HEALTH HAZARD: 1 FIRE HAZARD: 0 REACTIVITY: 0 PROTECTIVE EQUIPMENT: C		
MANUFACTURER'S NAME: ALLIED PRESSROOM CHEMISTRY.									
STREET ADDRESS 2040 LEE STREET, HOLLYWOOD, FLORIDA, 33020, USA									
OFFICE TELEPHONE: 800-327-8487		FAX: 954-923-6462		24 HR. EMERGENCY TELEP 800-424-9300 CHEMTRE			Safety Protective Glasses Gloves Apron		
THIS IS AN INDUSTRIAL CHEMICAL PRODUCT. ALL INDUSTRIAL CHEMICAL PRODUCTS POSE AN INHERENT HEALTH RISK. BEFORE USE ALWAYS READ COMPLETE LABEL AND MSDS FOR SAFE HANDLING PROCEDURES								APORS. DO NOT GET IN EYES, N CLOTHING. DO NOT INGEST	
SECTION 2 – INGREDIENT INFORMATION									
INGREDIENTS *These ingredients are subject to the reporting		%	•		HAZARD DATA				
requirements of SARA 313 and 40 CFR 372 Aliphatic petroleum distillates		50-70	64742-	-48-4 A	CGIH (TWA-TLV) 100p		ppm		
ALL INGREDIENTS ARE LISTED IN THE US TOXIC SUBSTANCE CONTROL ACT (TSCA)									
SECTION 3 - PHYSICAL DATA PHYSICAL STATE ODOR AND APPEARANCE WATER SOLUBILITY PH SPECIFIC GRAVITY									
		colorless lic	lorless liquid,		WATER SOLUBILITY Negligible		pplicable	SPECIFIC GRAVITY 0.81	
VAPOR PRESSURE (MM Hg) < 1 @ 20°C due to water	1 Hg) (AIR=1)		DENSITY		EVAPORATION RATE (Butyl acetate = 1) <1		NG POINT (°F) 166	V.O.C.'s 0 % by Mass 0 lb per Gallon (0 g/l)	
SECTION 4 - FIRE AND EXPLOSION DATA									
FLAMMABILITY YES ■ NO □ IF YES, UNDER WHICH CONDITIONS? * At temperatures above flash point									
						_	FIGHTING PROCEDURES: ed breathing apparatus if needed.		
FLASHPOINT (°F) AND METHOD 145 F TCC			_	MABLE LIMIT ME) : Unknown	LOWER FLAMMAE (% BY VOLUME): U				
AUTOIGNITION TEMPERATURE (°C) Not known			HAZARDOUS COMBUSTION PRODUCTS Oxides of carbon .						
EXPLOSION DATA * NOT KNOWN			SENSITIVITY TO IMPACT SENSITIVITY NO NO				Y TO STATIC DISCHARGE		
SECTION 5 - REACTIVITY DATA									
			CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION lone						
INCOMPATIBILTY WITH OTHER SUBSTANCES None known									
HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide This product is not phonoxide								otochemically reactive	



PRODUCT IDENTIFIER * ALLIED SLIP

SECTION 6 - TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY

SKIN CONTACT ■

SKIN ABSORPTION $\ \square$

EYE CONTACT ■

INHALATION

INGESTION ■

ACUTE EXPOSURE TO PRODUCT: Inhalation - Very low vapor pressure, negligible hazard Material may be misted when sprayed. Inhalation can cause irritation of nasal passages

Eye - Will cause irritation, burning, redness and tearing.

Skin - Can cause irritation, on prolonged contact.

Ingestion causes irritation of the digestive tract. Aspiration into the lungs can lead to pulmonary odema and chemical pneumonia which can prove fatal.

CHRONIC EXPOSURE TO PRODUCT: Prolonged skin contact may aggravate an existing dermatitis. Prolonged and repeated exposure to the pure solvent contained in this product has been reported to cause permanent brain and central nervous system damage

CARCINOGENICITY: No ingredient present at greater than 0.1 % is identified as a carcinogen by OSHA, IARC or NTP

TARGET ORGAN EFFECTS: Eye, skin irritant

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with running water for at least 15 minutes. Seek medical attention.

SKIN: wash affected area with soap and water. Remove contaminated clothing and launder before re-use.

INHALATION: Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical

INGESTION: Do not induce vomiting. Dilute by drinking water and seek immediate medical attention.

SECTION 7 - PREVENTATIVE MEASURES

GLOVES RESPIRATOR: Use NIOSH approved SCBA in EYE (SPECIFY)

Nitrile for incidental, non-immersion contact. emergency situations or confined areas. Splash proof goggles or face shield

CLOTHING: Boots, aprons, or chemical suits should be used when necessary to prevent skin contact.

ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS): No special requirements

LEAK AND SPILL PROCEDURE: Contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.

WASTE DISPOSAL: Contaminated vermiculite or porous surface must be disposed of in a permitted waste facility. Recovered liquids may be reprocessed or incinerated in a permitted waste facility. In all cases material should be disposed of in accordance with all applicable regulations.

HANDLING PROCEDURES AND EQUIPMENT: Keep container closed when not in use. Store only in closed, properly labeled containers. Store in a cool, dry, well ventilated area. Store as COMBUSTIBLE liquid. Treat empty containers as containing hazardous residues.

SECTION 8 - ADDITIONAL INFORMATION

CALIFORNIA PROPOSITION 65: This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness.

This product contains the following chemicals known by the state of California to cause cancer: None

This product contains the following chemicals known by the state of California to cause reproductive harm: None

SHIPPING INFORMATION: Not regulated for shipping purposes

SECTION 9 – PREPARATION AND DATE OF MSDS

PREPARED BY (GROUP DEPARTMENT, ETC.) ALLIED PRESSROOM CHEMISTRY TECHNICAL SERVICES DEPARTMENT

PHONE NUMBER 1-800-327-8487

DATE Sept 2010

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume risk of his use thereof.