

ALLIED PRESSROOM CHEMISTRY MATERIAL SAFETY DATA SHEET

		SECTIC)N 1	PRC	DUCT	IDEN	FIFICA	TION		JSE		
PRODUCT IDENTIFIER : ALLIED CA ULTRA WASH (Low VOC Blanket Wash for lithographic presses)									0-minimal, 1-slight, 2-moderate, 3-serious, 4-severe HEALTH HAZARD: 2 FIRE HAZARD: 3 REACTIVITY: 0 PROTECTIVE EQUIPMENT: C			
MANUFACTURER'S NAME: ALLIED PRESSROOM CHEMISTRY.												
STREET ADDRESS 2040 LEE STREET, HOLLYV	NOOD, I	FLORIDA, 3	33020,	USA					Ø	Q	Ш,	
OFFICE TELEPHONE: 800-327-8487		FAX: 954-923-6462				-	RGENCY TELEPHONE		Saf Glas		Gloves	Protective Apron
THIS IS AN INDUSTRIAL PRODUCTS POSE AN IN COMPLETE LABEL AND	HERE	NT HEAL	TH RIS	SK. B	EFORE U	SE ALW	AYS RE				VAPORS. D	O NOT GET IN EYES, ING. DO NOT INGEST
		SEC	CTIO	N 2	– INGR		IT INF	ORM	ATION			
INGREDIENTS *These ingredients are subject to the reporting requirements of SARA 313 and 40 CFR 372		%		CAS	CAS NUMBER		HAZARD DATA					
Acetone	Acetone		20-40		67-64-1		ACGIH (TLV) TWA 5					
	Methyl Acetate		20-40		79-20-0		ACGIH (TWA-TLV) 2					
Parachlorobenzotrifluoride		20-40		98-56-6			Not Establishe					_
Glycol Ether EB *		1-5		111-76-2			ACGIH (TLV) TWA					
Petroleum Distillates		1-5			64742-89-8		ACGIH (TWA-TLV) –1 S TOXIC SUBSTANCE C					
	ALL IN	GREDIENT								ACT (TSC	A)	
					ION 3 -			DATA				
PHYSICAL STATE LIQUID	ODOR AND APP Clear colorless lig Fruity/Ketone odd		uid, Partial			Solubili	OLUBILITY PH No		H ot applicable		SPEC 0.95	IFIC GRAVITY
VAPOR PRESSURE (MM Hg) of VOC < 5mmHg @ 20°C	VAPO (AIR= >1	POR DENSITY R=1)		EVAPORAT (Butyl aceta <1		-	tate = 1) 132		ILING POINT (°F) 2 – 340			.'s less exempt cpds o per Gallon
		SEC	CTIO	N 4	- FIRE /	AND E	XPLO	SION	DATA			
FLAMMABILITY YES ■ NO □	FLAMMABILITY IF YES, UNDER											
EXTINGUISHING MEDIA CARBON DIOXIDE, DRY CHEMICAL, UNI				AL F	OAM.	-	SPECIAL FIRE FIG					
FLASHPOINT (°F) AND METHOD < 4 F by TCC			UPPER FLAMM (% BY VOLUM				E) : Unknown		LOWER FLAMMABLE LIMIT (% BY VOLUME): Unknown			
AUTOIGNITION TEMPERATURE (°C) Not known			HAZARDOUS COMBUSTION PRODUCTS Oxides of carbon and hydrocarbons.									
EXPLOSION DATA * NOT KNOWN			SENSITIVITY TO IMPACT - NO				SENSITIVITY TO STATIC			ISCHAR	GE	
			SE	СТІ	ON 5 - F	REAC	ΓΙVΙΤΥ	' DAT	Α			
CHEMICAL STABILITY CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION YES NO □												
INCOMPATIBILTY WITH Strong oxidizing agents, s				5								
HAZARDOUS DECOMPOSITION PRODUCTS: In contact with open flame or incandescent material will liberate carbon dioxide, carbon monoxide and hydrocarbons							Th	nis produc	t is non-	photocher	nically reactive	



STOOM CHEM								
PRODUCT IDENTIFIER * ALLIED CA ULTRA WASH								
SECTION 6 - TOXICOLOGICAL PROPERTIES								
ROUTES OF ENTRY SKIN CONTACT ■ SKIN ABSORPTION ■ EYE CONTACT ■ INHALATION ■ INGESTION ■								
ACUTE EXPOSURE TO PRODUCT: Inhalation - Inhalation can cause severe irritation of the respiratory tract, signs of central nervous system depression, dizziness nausea and headache. Eye - Will cause severe irritation, burning, redness and tearing. Skin - Can cause irritation, redness burning and drying. Ingestion causes irritation of the digestive tract. Aspiration into the lungs can lead to pulmonary odema and chemical pneumonia which can prove fatal. Prolonged over-exposure can lead to narcosis, respiratory failure , coma.								
CHRONIC EXPOSURE TO PRODUCT : Prolonged skin contact may aggravate an existing dermatitis. Prolonged and repeated exposure to the pure solvent contained in this product has been reported to cause permanent brain and central nervous system damage.								
CARCINOGENICITY: No ingredient has been identified as carcinogenic or potentially carcinogenic by IARC, NTP, OSHA								
TARGET ORGAN EFFECTS: Eyes, skin irritation. Kidneys, blood, liver and lung effects on prolonged over-exposure								
 EMERGENCY FIRST AID PROCEDURES: EYES: Flush with running water for at least 15 minutes. Seek medical attention. SKIN: wash affected area with soap and water. Remove contaminated clothing and launder before re-use. INHALATION: Remove victim to fresh air. Administer oxygen and/or artificial respiration if breathing difficulties occur. Seek medical attention. INGESTION: Do not induce vomiting. Material is an aspiration hazard, may enter lungs and cause lung damage. Seek immediate medical attention. 								
SECTION 7 - PREVENTATIVE MEASURES								
GLOVES RESPIRATOR: Use NIOSH approved SCBA in bitrile for incidental, non-immersion contact. EYE (SPECIFY) Splash proof goggles or face shield Splash proof goggles or face shield								
CLOTHING : Boots, aprons, or chemical suits should be used when necessary to prevent skin contact.								
ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) : Use local exhaust or dilution ventilation as appropriate to control exposure below permissible levels. Vapors are heavier than air and will collect in low areas								
LEAK AND SPILL PROCEDURE : Extinguish all sources of ignition. Provide maximum ventilation. Dike area to contain spill. Take precautions to prevent contamination of ground and surface waters. Recover spilled material using absorbent material such as vermiculite and sweep into closed containers for disposal.								
WASTE DISPOSAL : Contaminated vermiculite or porous surface must be disposed of in a permitted hazardous waste facility. Recovered liquids may be reprocessed or incinerated in a permitted hazardous waste facility. In all cases material should be disposed of in accordance with all applicable regulations.								
HANDLING PROCEDURES AND EQUIPMENT: Keep container closed when not in use. Store only in closed, properly labeled containers. Store as VERY FLAMMABLE LIQUID. Store in a cool, dry, well ventilated area away from heat sparks and open flames. Treat empty containers as containing hazardous residues.								
ADDITIONAL INFORMATION								
CALIFORNIA PROPOSITION 65: This regulation does not address "de minimis" levels. Therefore even trace amounts of chemicals on these lists must be identified. Trace quantities refer low levels of materials whose exact concentrations may not always be determined because of their minuteness. This product contains the following chemicals known by the state of California to cause cancer : benzene, acetaldehyde, formaldehyde, ethylene oxide. This product contains following chemicals known by the state of California to cause reproductive harm : benzene, ethylene oxide								
SHIPPING INFORMATION: Flammable liquids, NOS (acetone, methyl acetate), 3, UN 1993, PG II								

SECTION 9 - PREPARATION AND DATE OF MSDS

PREPARED BY (GROUP DEPARTMENT, ETC.)	PHONE NUMBER	DATE
ALLIED PRESSROOM CHEMISTRY TECHNICAL SERVICES DEPARTMENT	1-800-327-8487	Sept 2010

The above information is believed to be correct as of the date hereof and is based on data supplied by raw material suppliers, however, no warranty of merchantability, fitness for use, or any other warranty is expressed or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with each use. Since the information contained herein may be applied under conditions beyond our control and with which we are unfamiliar, and since the data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its' use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume risk of his use thereof.