

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 955-002P

Product name Anti-Static Spray

Effective date 10-Feb-2011

Company information Sprayway, Inc. 484 Vista Ave.

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 01

2. Hazards Identification

Emergency overview FLAMMABLE

Aerosol. CONTENTS UNDER PRESSURE.

Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Prolonged

exposure may cause chronic effects.

Potential health effects

Routes of exposure Eye contact. Inhalation. Skin contact. Ingestion.

Eyes Contact may irritate or burn eyes.

Skin Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Liver. Lungs.

Chronic effects Liver injury may occur. May cause central nervous system disorder (e.g., narcosis

involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. Can cause adverse reproductive effects - such as birth defects, miscarriages, or infertility. Frequent or prolonged contact may defat and dry the skin,

leading to discomfort and dermatitis. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Narcosis. Coughing. Liver enlargement. Jaundice. Defatting of

the skin. Skin irritation.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Ethyl Alcohol	64-17-5	70 - 80
1,1-Difluoroethane	75-37-6	15 - 20
Non-hazardous and other components below reportable levels		0.1 - 1

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with warm water and

soap. Get medical attention if irritation develops and persists.

Inhalation Move to fresh air. Do not use mouth-to-mouth method if victim inhaled the substance.

Call a physician if symptoms develop or persist.

Product name: Multi-Purpose Anti-Static Spray

Product #: 955- Anti-Static Spray

Ingestion

If material is ingested, immediately contact a poison control center. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Notes to physician

Keep victim warm. Keep victim under observation. Symptoms may be delayed.

5. Fire Fighting Measures

Flammable properties

Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Protective equipment and precautions for firefighters Water. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

In case of fire and/or explosion do not breathe fumes. Containers should be cooled with water to prevent vapor pressure build up. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures

Methods for containment

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. After removal flush contaminated area thoroughly with water.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not smoke while using or until sprayed surface is thoroughly dry. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not re-use empty containers. Do not get this material in contact with eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Keep away from food, drink and animal feedingstuffs. Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Ethyl Alcohol	64-17-5	1000 ppm	1000 ppm	Not established
OSHA				
Components	CAS#	TWA	STEL	Ceiling

1000 ppm

Personal protective equipment

Eye / face protection

Ethyl Alcohol

Do not get in eyes. Chemical goggles are recommended.

Skin protection

Wear appropriate chemical resistant clothing. Chemical resistant gloves.

Respiratory protection

Wear positive pressure self-contained breathing apparatus (SCBA). If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Not established

Not established

9. Physical & Chemical Properties

Appearance

Compressed liquefied gas.

64-17-5

Product name: Multi-Purpose Anti-Static Spray

MSDS US Product #: 955-Anti-Static Spray

Boiling point 136.4 °F (57.8 °C) estimated

Color clear colorless

Density 0.8114 g/cm3 estimated **Flammability (HOC)** 21.0417 kJ/g estimated

Flash back Yes

Flash point -58 °F (-50 °C) Propellant

Form Aerosol.
Freezing point Not available
Odor Characteristic.
pH Not applicable

Physical state Liquid.

Pressure 27 - 37 psig @70F

Solubility Negligible Specific gravity 0.8115

10. Chemical Stability & Reactivity Information

Chemical stability Material is stable under normal conditions. Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effects Acute LC50: 157 mg/l/4h estimated, Rat, Inhalation

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

1,1-Difluoroethane 75-37-6 Inhalation LC50 Mouse 977 g/m3 2 h

Ethyl Alcohol 64-17-5 Oral LD50 Rat 7060 mg/kg; Inhalation LC50 Rat 124.7 mg/L 4 h

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity

IARC - Group 1 (Carcinogenic to Humans)

Ethyl Alcohol 64-17-5 Monograph 100E [in preparation] (in alcoholic beverages); Monograph 96 [in

preparation] (in alcoholic beverages)

Reproductive effects Hazardous by OSHA criteria. Can cause adverse reproductive effects - such as birth

defects, miscarriages, or infertility.

Teratogenicity Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity Components of this product have been identified as having potential environmental

concerns.

LC50 16191 mg/L, Fish, 96.00 Hours, EC50 14503 mg/L, Daphnia, 48.00 Hours,

IC50, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Dispose of this material and its container to hazardous or

special waste collection point. Do not incinerate sealed containers. If discarded, this

product is considered a RCRA ignitable waste, D001.

Product name: Multi-Purpose Anti-Static Spray

Product #: 955- Anti-Static Spray

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306 156, 306 Packaging non bulk None Packaging bulk

IMDG

Basic shipping requirements:

Proper shipping name **AEROSOLS**

Hazard class 21 **UN** number 1950

Additional information:

Packaging exceptions LTD QTY Item 5F None Labels required **Transport Category** 2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class 2.1 **UN** number 1950

Additional information:

LTD QTY Packaging exceptions Labels required 2.1





15. Regulatory Information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US** federal regulations

Standard, 29 CFR 1910.1200.

CERCLA/SARA Hazardous Substances - Not applicable.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Ethyl Alcohol 64-17-5 Present

16. Other Information

HMIS® is a registered trade and service mark of the NPCA. **Further information**

Health: 1* **HMIS®** ratings

Flammability: 3 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and

experience currently available.

Prepared by Regulatory Compliance