Product Code: **3462Q, 3462S**

MATERIAL SAFETY DATA SHEET

Comply with OSHA'S Hazard Communication Standard, 29 CFR 1910.1200.

HMIS RATING: HEALTH = 2 FLAMMABILITY = 2 REACTIVITY = 0 PROTECTION = B

NFPA RATING: HEALTH = 2 FLAMMABILITY = 2 REACTIVITY = 0

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRINTERS PRIDE® CHROME CYLINDER CLEANER AND DESENSITIZER

Manufacturer: Burnishine Graphic Products Emergency Contact: 1-800-535-5053 (24 hours) or

25392 West Park Court contact your regional Poison Control. Lake Villa. IL 60046

Printed:

Page:

10/13/2009

1 of 2

847-356-2553

MSDS Issue Date: 09/01/09

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

	CAS	Wt %	OSHA	ACGIH	Other Limits
<u>Component</u>	<u>Number</u>	(optional)	<u>PEL</u>	<u>TLV</u>	Recommended
Ethylene Glycol Monobutyl Ether	111-76-2		50 ppm skin	20 ppm	
Ethylene Glycol	107-21-1		N/D	100 mg/m ³ aerosol	
Aliphatic Hydrocarbon	64742-48-9		100 ppm	100 ppm	

SECTION 3 – HAZARD IDENTIFICATION

Routes of Entry: Skin contact, skin absorption, eye contact, ingestion.

Effects of Acute Exposure:

Inhalation: Prolonged exposure to vapors may cause irritation to nose, throat, and respiratory tract.

Eyes: Contact will cause irritation.

Skin: May be absorbed through skin. Prolonged or repeated contact may cause irritation. **Ingestion:** Accidental ingestion will cause irritation to mouth, stomach, and digestive tract.

Effects of Chronic Exposure: None known.

Medical Conditions Generally Aggravated by Exposure: Dermatitis and other pre-existing skin conditions.

Carcinogenicity: NTP:N/A IARC Monographs: N/A OSHA Regulated: N/A

SECTION 4 - FIRST AID MEASURES

Inhalation: Remove to fresh air. If person is having difficulty breathing, give oxygen and call a physician immediately.

Eyes: Rinse with water for at least 15 minutes. If irritation persists, seek medical attention immediately.

Skin: Wash with soap and water. If irritation persists, seek medical attention.

Ingestion: Rinse mouth with water. Drink 1-2 glasses of water. Get medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point (Method Used): 127°F TCC

Flammable Limits: N/A

Autoignition Temperature: N/A

Extinguishing Media: Water spray, foam, dry chemical, and carbon dioxide.

Special Fire Fighting Procedures: Use NIOSH approved self-contained positive pressure breathing apparatus and

protective clothing. Use water spray to cool fire-exposed containers.

Unusual Fire and Explosion Hazards: None.

<u>SECTION 6 – ACCIDENTAL REL</u>EASE MEASURES

Steps to Be Taken in Case Material is Released or Spilled: Absorb spill with dry absorbent. Wash the contaminated area with soap and water.

SECTION 7 – HANDLING AND STORAGE

Precautionary Information: For industrial use only. Keep out of reach of children.

Handling and Storage Conditions: Keep container closed when not in use. Store in a cool, dry area. Store away from heat, flames, and electrical sparks.

SECTION 8 – EXPOSURE CONTROL / PERSONAL PROTECTION

Ventilation: General ventilation normally adequate.

Respiratory Protection (Specific Type): None required under normal use conditions.

Document No.: 051007-2 Issue Date: 01/16/06 Product Code: **3462Q, 3462S**

MATERIAL SAFETY DATA SHEET

Comply with OSHA'S Hazard Communication Standard, 29 CFR 1910.1200.

Printed:

Page:

10/13/2009

2 of 2

Protective Gloves: Latex, nitrile, or rubber.

Eye Protection: Safety glasses.

Other Protective Clothing or Equipment: None.

Work/Hygienic Practices: None.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Color: Muddy blue.Product State: Liquid.Odor: Glycol.Boiling Point: N/D

Specific Gravity (H₂O = 1): 1.01 Vapor Pressure (mm Hg.): N/D Melting Point: N/A Vapor Density (AIR = 1): N/D Evaporation Rate (Butyl Acetate = 1): N/A Solubility in Water: Partial.

VOC: 23.67%, 238.5 g/L, 1.99 lb/gal

SECTION 10 – STABILITY AND REACTIVITY

Stability: Stable.

Incompatibility (Materials to Avoid): Strong oxidizing agents.

Hazardous Decomposition or By-products: May include and are not limited to oxides of carbon.

Hazardous Polymerization: Will not occur.

Conditions to Avoid: None.

SECTION 11- TOXICOLOGICAL INFORMATION

Toxicological Data: N/A

SECTION 12- ECOLOGICAL INFORMATION

Environmental Data: N/A

SECTION 13- DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

SECTION 14- TRANSPORTATION INFORMATION

DOT Regulations (Ground): Hazardous. Exempt from labeling, limited quantity 173.150.

IATA Regulations (Air): Hazardous.

Proper Shipping Name: Combustible liquid, n.o.s. **Hazard Class Number and Description:** 3

UN/NA Number: NA1993

Packaging Group: III

SECTION 15- REGULATORY INFORMATION

All ingredients in this product are listed or are excluded from listing on the US Toxic Substances Act (TSCA) Chemical Substance Inventory.

SARA Title III, Section 313 reportable chemicals: ethylene glycol monobutyl ether, ethylene glycol.

SECTION 16 – OTHER INFORMATION

Additional Information: Use as directed.

Note: N/A or N/D as an information entry means the data is not applicable or determined, respectively.

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the information contained within. Actual conditions of use, handling, storage, and disposal are beyond manufacturer's control. User is responsible to evaluate all available information when using this product for any particular use and to comply with local, state, and federal regulations.

Document No.: 051007-2 ssue Date: 01/16/06