

Date: 1/31/2009

	H	M	I	S	
	Hazard Ratings			Health	2
Minimal Slight	0 1	Serious Severe	3 4	Flammability	1
Slight Moderate	2	20.010	-	Reactivity	0

HOLLAND INK CORPORATION OF AMERICA
185 Oval Drive Islandia, NY 11749

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America MANUFACTURER:

185 Oval Drive Islandia, NY 11749

Emergency Telephone: 631-715-7000 Product Class: Printing ink additive Trade Name: Aqua Flo Varnish #30 Tower Products, Inc.

2703 Freemansburg Ave., Easton PA 18045 Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer s Code ID: V2159

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Solid Resins/Oil Varnish			N/A	N/A	No
New Jersey Trade Secret					
CAS/Registry Trade Secret Numbers					
provided on request by manufacturer					

3. HAZARDS IDENTIFICATION

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact Direct contact may cause irritation.

Skin Contact Prolonged contact or repeated exposure may cause irritation.

Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation of nasal and respiratory passages. Inqestion May cause questrointestinal irritation.

Medical Conditions aggravated by normal exposure Persons with dermatitis should avoid skin contact.

Target Organs Skin, eyes, lungs.

Primary Routes of entry Eyes, inhalation, dermal.

EMERGENCY FIRST AID PROCEDURES

Eye Contact Gently flush with large amounts of water until initation subsides. If inritation persists, contact a physician. Skin Contact Remove contaminated clothing and wash thoroughly before reusing. Wash affected skin areas with soap and water.

Seek medical attention if irritation persists

Ingestion If swallowed, do not induce vaniting. Call a physician or poison control center.

Inhalation Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point	.Above 310 F Method used: closed cup
Explosion Limits	
Extinguishing Media	. Foam, carbon dioxide, dry chemical fire apparatus. Water spray may be
3 3	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon Monoxide and
-	Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: W ipe up. Dispose of wipes in approved waste containers for flammable liquids. If petroleum hydrocarbon is used, provide sufficient ventilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use.

Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation Use sufficient ventilation.

Protective Gloves Impermeable gloves recommend-

ed to prevent skin irritation and absorption.

Respiratory Protection Nane required.

Eye Protection Safety glasses recommended.

Other Protection None recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 0 lbs./qallon

Boiling Range °F:> N/A Vapor Density vs. Air: Heavier

Density: 8.40 lbs./gallon ASTM D1475

Type of Odor: Resinous Appearance: Viscous liquid

Evaporation Rate vs. Butyl Acetate: Slower

Percentage Volatile By Weight: 0-1% ASTM D2369

O Grams/liter Method 24 Freezing Point °F: N/A Vapor Pressure: .N/A Specific Gravity: 1.02 Odor Threshold: High

pH: N/A

Coefficient of Water/oil Distribution: N/A

10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents, acids and bases. Avoid storage above 90 F.

Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and smoke.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

International Agency for Research on Cancer (IARC) or OSHA.

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION DOT (HM 181): Not required

Shipping Labels: None required

15. REGULATORY INFORMATION

CERCLA Superfund 40CFR 117.302 Contains no reportable materials

approval for direct or indirect contact with food.

EINECS (European Economic Community) All impredients listed.

CONEG Legislation Meets all current State and Heavy Metal limitations.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.