

Material Safety Data Sheet - Van Son Fountain Stimulator Date 1/31/2009

	H	M	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 0 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America M

185 Oval Drive Islandia, NY 11749

Emergency Telephone: 631-715-7000

Product Class: Printing Ink Additive

Trade Name: Van Son Fountain Stimulator

 $\verb|MANUFACTURER: Tower Products, Inc.|$

2703 Freemansburg Ave.

Easton, PA 18045

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer s Code ID: V2153

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Cobalt Acetate Tetrahydrate	71-48-7	8-15	.05mg/M3	.05mg/M3	No

3. HAZARDS IDENTIFICATION

FFFFCTC OF OVEDFYDOCIDE

4. FIRST AID MEASURES

	EFFECIS OF OVEREXPOSURE			
Eye Contact	Direct contact may cause irritation.			
Skin Contact	Prolonged contact or repeated exposure may cause minor irritation.			
Inhalation	Excess inhalation of mist or vapor may cause dizziness, nausea or irritation			
	of nasal and respiratory passages.			
Ingestion	May cause gastrointestinal irritation.			
Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact.				
Target Organs:	Skin, eyes, lungs.			
Primary Routes of entryEyes, inhalation, dermal.				
	EMERGENCY FIRST AID PROCEDURES			
Eye Contact	Flush with large amounts of water until irritation subsides.			
	Einitation persists, contact a physician.			
Skin Contact:	W ash with soap and water. Remove contaminated clothing and wash			
	thoroughly before reusing.			
Ingestion	If swallowed, do not induce vomiting. Call a physician.			
Inhalation	Remove individual to fresh air			

5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	LEL: N/A UEL: N/A
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: W ipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use.

Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. Eye Protection: Goggles recommended.

Protective Gloves: Gloves recommended. Other Protection: None required.

Respiratory Protection: None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 0 lbs./gallon 0 Grams/liter Method 24

Boiling Range °F:> 200 Freezing Point °F: -10 F

Vapor Density vs. Air: Heavier Vapor Pressure: less than 0.04ps.

Density: 8.35 lbs./gallon ASTMD1475 Specific Gravity: 1.01 Type of Odor: Acetic Odor Threshold: Low

Appearance: Ruple liquid pH: N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 90% ASTM D2369

10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F.

Keep containers closed when not in use.

Hazardous Decomposition Products: None. Hazardous Polymerization: Willnot cour.

11. TOXICOLOGICAL INFORMATION

National Toxicology Program (NIP), or the International Agency for Research on

Cancer (IARC).

Mutagen No
Teratogen No
Reproductive Toxicity No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION - DOT (HM 181): Not required Shipping Labels: None required

15. REGULATORY INFORMATION

EINECS (European Economic Community) All ingredients listed.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.