

Material Safety Data Sheet -PANTONE Fluorescent Colors Date 11/30/2006

	н	М	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America 185 Oval Drive Islandia, NY 11749 Emergency Telephone:631-715-7000 Product Class: Fluorescent Of fæt Ink Trade Name: Pantone Fluorescent Colors

Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: 78801 through 78807

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNO.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Dyed Polymer Dispersion	Propriet ary	80-85	N/A	N/A	No
Technical White Oils	8042-47-5	10-15	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHAHazard Communication 29 CFR 1910.1200Nme

4. FIRST AID MEASURES

	EFFECTS OF OVEREXPOSURE		
Eye Contact	Direct contact may cause inritation.		
Skin Contact	Prolonged contact or repeated exposure may cause minor irritation.		
Inhalation	Excess inhalation of mist or vapor may cause dizziness, nausea or irritation		
	of nasal and respiratory passages.		
Ingestion	May cause gastrointestinal inritation.		
Medical Conditions aggravated by	normal exposure: Persons with dermatitis should avoid skin contact.		
Target Organs:	Skin, eyes, lungs.		
Primary Routes of entry Eyes, inhalation, dennal.			
	EMERGENCY FIRST AID PROCEDURES		
Eye Contact	Flush with large amounts of water until inritation subsides.		
	If initation persists, contact a physician.		
Skin Contact:	W ash with soap and water. Remove contaminated clothing and wash		
	thoroughly before reusing.		
Ingestion	If swallowed, do not induce vomiting. Call a physician.		
Inhalation	Remove individual to fresh air.		

5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method used: closed cup
Explosion Limits	LEL: N/A UEL: N/A
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion prod-
irts	

uts

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient vertilation. W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Avoid storage above 90 F. Keep containers closed when not in use. None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Protective Gloves: Respiratory Protection: Use sufficient vertilation. Gloves recommended. None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.20 lbs./gallon Boiling Range °F:> N/A Vapor Density vs. Air: Heavier Density: 7.90 lbs./ gallon ASTMD1475 Type of Odor: Essentially colorless Appearance: Brightly colored viscous paste. Evaporation Rate vs. Butyl Acetate: Slower Percentage Volatile By Weight: 14% ASTMD2369

10. STABILITY AND REACTIVITY

Product Stability: Stable Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F. Keep containers closed when not in use.

Eye Protection: Other Protection: Goggles recommended. None required.

140 Grams/liter Method 24 Freezing Point °F: N/A Vapor Pressure: less than 0.04psi Specific Gravity: .95 Odor Threshold: High pH: N/A Coefficient of Water/oil Distribution: N/A

Hazardous Decomposition Products: None. Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

TeratogenNo Reproductive ToxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply.Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

The information and recommendations contained herein are based on standard product and are proprietary and furnished solely for the use of our customers. Since it is impossible for us to determine the precise conditions under which our products will be used, neither MC nor its affiliates can accept responsibility for loss, injury or other damages resulting from the use of the product or this or any information provided by us. Users are advised to make their own tests to determine the safety, suitability and relevance of Federal and local law to the product as it is to be used by them. Therefore, unless otherwise agreed in a signed writing, no guarantees of any kind, including those of fitness or merchantability, are made by MC Company or its affiliates with regard to any of their product s Prepared by: DamenBiarthi

This information is furnished without warranty, express or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data