

# Material Safety Data Sheet -Van Son Gloss Overprint Varnish Date 11/30/2006

	H	M	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America

185 Oval Drive Islandia, NY 11749

Emergency Telephone: 631-715-7000

Product Class: Gloss Overprint Varnish

Trade Name: Van Son Gloss Overprint Varnish

MANUFACTURER:

Lawter International Inc. (Hexion)

8601 95th St., Pleasent Prairie, WI 53158 Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: V2174-2175, V2180-2181

V2156, V2178-2179

## 2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Hydrotreated Middle Distillate	Trade Secret	Trade Secret	5mg/M3	5mg/M3	No
Pennsylvania and New Jersey:					
Trade Secret					
Ingredients Partially Unknown					

### 3. HAZARDS IDENTIFICATION

#### 4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE of nasal and respiratory passages. Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact. Primary Routes of entry ...... Eyes, inhalation, dermal. EMERGENCY FIRST AID PROCEDURES If initation persists, contact a physician. thoroughly before reusing. 

## 5. FIRE FIGHTING MEASURES

Flash Point	.Above 240 F Method used: closed cup
Explosion Limits	
<del>-</del>	. Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	.Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	. Self-contained breathing apparatus recommended.

#### 6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

#### 7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use.

Other Precautions: None required.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. Eye Protection: Goggles recommended.

Protective Gloves: Gloves recommended. Other Protection: None required.

Respiratory Protection: None required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 3.20 lbs./gallon 300 Grams/liter Method 24

Boiling Range °F:> 465-515 Freezing Point °F: N/A
Vapor Density vs. Air: Heavier Vapor Pressure: N/A
Density: 7.9 lbs./ gallon ASTM D1475 Specific Gravity: 0.95
Type of Odor: Oleoresinous Odor Threshold: High

Appearance: Amber viscous paste. ph: N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 35% ASTM D2369

#### 10. STABILITY AND REACTIVITY

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F.

Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and smoke.

Hazardous Polymerization: Will not occur.

## 11. TOXICOLOGICAL INFORMATION

Toxicology

Program (NTP).

## 12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

#### 13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

#### 14. TRANSPORT INFORMATION - DOT (HM 181): Not required Shipping Labels: None required

#### 15. REGULATORY INFORMATION

SARA Title III ......None

direct or indirect contact with food.

EINECS (European Economic Community) ..... All ingredients listed.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.