

Material Safety Data Sheet Quickson Pro Series Colors

Т

S

Reactivity

Flammability 1

1

0

Health

Date: 11/30/2006

Hazard Ratings

м

 \mathbf{H}

Material Safety and Data Sheet prepared by Wim De Boer

Van Son Holland Ink Corporation of America

Minimal0Serious3d by Wim De BoerSlight1Severe4Moderate22

MANUFACTURER: VAN SON OF SOUTH KOREA

Chemtrec 24 Hour Emergency No-800-424-9300

185 Oval Drive Islandia, NY 11749 Emergency Telephone: 631-715-7000

Product Class: Offset Ink Oxidizing Colors

1.

DISTRIBUTOR:

Quickson Pro Series Colors: VS3110, VS3111, VS3112

2. INGREDIENT COMPOSITION INFORMATION

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Ingredient	CASNo.	W T %	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Organic Pigments	See Table 2	25 - 40	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	15 - 20	N/A	N/A	No
Vegetable Oils, includes Linseed Oil	Various	25 - 35	N/A	N/A	No
Hydrotreated, Light Paraffin	64742-55-8	15 - 25	5mg/M3	5mg/M3	No
C15 - 30					
Cobalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	8030-70-4	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2 - 4	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 Manganese Compound

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE

Eye Contact	Direct contact may cause irritation.
Skin Contact	. Prolonged contact or repeated exposure may cause irritation.
Inhalation	Excess inhalation of mist or vapor may cause dizziness, nausea or irrita
	tion of nasal and respiratory passages.
Ingestion	May cause gastrointestinal irritation.
	normal exposure: Persons with dematitis should avoid skin contact.
Target Organs:	Skin, eyes, lungs.
Primary Routes of entry	Eyes, inhalation, dermal.
	-

EMERGENCY FIRST AID PROCEDURES

Eye Contact	Flush with large amounts of water until irritation subsides.
-	finitation pensists, contact a physician.
Skin Contact:	W ash with soap and water. Remove contaminated clothing and wash
	thoroughly before reusing.
Ingestion	. If swallowed, do not induce vomiting. Call a physician.
Inhalation	Remove individual to fresh air.

5. FIRE FIGHTING MEASURES

Flash Point	Above 250 F Method Used: Closed Cup
Explosion Limits	LEL: N/A UEL: N/A
Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
	applied to cool exposed closed containers.
Unusual Fire and Explosion Hazards	Dense smoke may be generated when burning. Carbon
	Monoxide and Carbon Dioxide generated as combustion products
Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released:W ipe up. Dispose of wipes in approved waste containers. If petroleum Hydrocarbon is used, provide sufficient ventilation. W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling:Avoid storage below 32 & above 90 F. Keep containers closed when not in use.Other Precautions:None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation:	Use sufficient ventilation.
Protective Gloves:	Gloves recommended.
Respiratory Protection:	None required.
Eye Protection:	Goggles recommended.
Other Protection:	None recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Viscous Paste	pH-Value	:	N/A	
Color	· Various	Freezing Pt./Range	:	N/A	
Odor	: Oily	Boiling Pt./Range	:	>500 F	
Odor Threshold	: N/A	Specific Gravity	:	1.00 - 1.05	68 F
Volatile Organic					
Compounds	: 12 - 18%	Autoignition Temp.	:	N/A	
Evaporation Rate					
vs. Butyl Acetate	: Slover	Vapor Pressure	:	<0.04 psi	68 F
Vapor Density vs Air :	: Heavier	Solubility in Water	:	N/A	

10. STABILITY AND REACTIVITY

Product Stability: Stable Conditions to Avoid: Strong oxidizing agents Avoid storage below 32 & above 90 F. Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and Smoke.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by

National Toxicology Program (NIP), International Agency for Research on Cancer (IARC) or OSHA.

MutagenNo TeratogenNo

Reproductive ToxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION

DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATO RY INFORMATION

TSCA (Toxic Substance Control Act) All ingredients listed in TSCA Inventory		
CERCLA Superfund 40CFR 117.302 Contains no reportable materials		
SARA Title IIINone		
FDAThis printing ink is not a food additive and would not have		
approval for direct or indirect contact with food.		
EINECS (European Economic Community) All ingredients listed.		
California Proposition 65None		
CONEG Legislation Meets all current State and Heavy Metal limitations.		
Canadian WHMIS		
Vegetable Ink Printing Act of 1994 Meets the 20% minimum requirement of vegetable oil in		
sheet fed inks		

This information is furnished without warranty, express or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.