

Rubber Base Plus Black Material Safety Data Sheet

Date 11/30/2006

	H	M	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

DISTRIBUTOR: Van Son Holland Ink Corporation of America

185 Oval Drive Islandia, NY 11749

Emergency Telephone: 631-715-7000

Product Class: Offset Black Ink Non-oxidizing

Trade Name: Rubber Base Plus Black 10850/12630,

PANTONE Black

MANUFACTURER:

Van Son Royal Dutch Printing Ink Factories,

Hilversum, Holland

Chemtrec 24 Hour Emergency No-800-424-9300 Manufacturer s Code ID: VS101/151 VS102/152,

VS310/510

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	
Carcinogen					
Carbon Black	1333-86-4	15-25	3.5 mg/M3	3.5 mg/M3	No
Organic Pigments	Various	2-10	3.5 mg/M3	3.5 mg/M3	No
Synthetic Resins	Various	30-50	N/A	N/A	No
Naphthenic Severe Hydrotreated					
Middle Distillate	64742-53-6	15-20	5mg/M3	N/A	No
Vegetable Oil Includes		20-30	N/A		
Linseed Oil	8001-26-1		<u> </u>		
Sova Oil	8001-22-7				

3. HAZARDS IDENTIFICATION

4. FIRST AID MEASURES

EFFECTS OF OVEREXPOSURE Eye Contact Direct contact may cause irritation. tation of nasal and respiratory passages. Medical Conditions aggravated by normal exposure: Persons with dermatitis should avoid skin contact. Target Organs: Skin, eyes, lungs. Primary Routes of entry Eyes, inhalation, dermal. EMERGENCY FIRST AID PROCEDURES Himitation persists, contact a physician. thoroughly before reusing.

5. FIRE FIGHTING MEASURES

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: W ipe up. Dispose of wipes in approved waste containers.

If petroleum hydrocarbon is used, provide sufficient ventilation.

W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Avoid storage above 90 F. Keep containers closed when not in use.

Other Precautions: None required.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Use sufficient ventilation. Eye Protection: Goggles recommended.

Protective Gloves: Gloves recommended. Other Protection: None required.

Respiratory Protection: None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 1.32 lbs./gallon 158 Grams/liter Method 24

Boiling Range °F:> 570 Freezing Point °F: N/A

Density: 8.77 lbs./gallon ASTMD1475 Specific Gravity: 1.05
Type of Odor: Oily Odor Threshold: High

Appearance: Black viscous paste.

pH: N/A

Evaporation Rate vs. Butyl Acetate: Slower Coefficient of Water/oil Distribution: N/A

Percentage Volatile By Weight: 16% ASTM D2369

Product Stability: Stable

Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F.

Keep containers closed when not in use.

Hazardous Decomposition Products: Carbon Monoxide, Carbon Dioxide and Smoke.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

10. STABILITY AND REACTIVITY

National Toxicology Program (NIP), or the International Agency for Research on

Cancer (IARC).

Mutagen No
Teratogen No
Reproductive Toxicity No

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental prob-

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181): Not required Shipping Labels: None

15. REGULATORY INFORMATION

CERCLA Superfund 40CFR 117.302 Contains no reportable materials

SARA Title IIINone

approval for direct or indirect contact with food.

EINECS (European Economic Community) All ingredients listed.

Vegetable Ink Printing Act of 1994Meets the 20% minimum requirement of vegetable oil in sheet fed inks

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.