

Material Safety Data Sheet - SonaPrint Black

Date 11/30/2006

	н	М	I	S	
Minimal Slight Moderate	Hazard 0 1 2	Ratings Serious Severe	3 4	Health Flammability Reactivity	1 1 0

Van Son Royal Dutch Printing Ink Factories,

Chemtrec 24 Hour Emergency No-800-424-9300

Manufacturer s Code ID: VS850, VS854, VS856

MANUFACTURER:

Hilversum, Holland

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANU FACTURER: Van Son Holland Ink Corporation of America

185 Oval Drive Islandia, NY 11749 Emergency Telephone: 631-715-7000 Product Class: Of fset Black Ink Oxidizing

Trade Name: SonaPrint PANTONE Black, Process & Intense Black

2. INGREDIENT COMPOSITION INFORMATION

Ingredient	CASNo.	WT%	OSHA (PEL)	ACGIH (TLV)	Carcinogen
Carbon Black	1333-86-4	15-30	3.5mg/M3	3.5mg/M3	No
Organic Pigments	See Table 2	2-10	3.5mg/M3	3.5mg/M3	No
Synthetic Resins	Various	20-40	N/A	N/A	No
Vegetable Oil Includes	Various	12-20	N/A	N/A	No
Linseed Oil	8001-26-1				
Soy Oil	8001-22-7				
Severe Acid Treated	64742-13-8				
or Solvent Refined Middle Distillate	64741-91-9	20-40	5mg/M3	N/A	No
Cobalt Drier	61789-52-4	0-1	0.1mg/M3	N/A	IARC
Manganese Drier	8030-70-4	0-1	5mg/M3	N/A	No
Polymeric Wax Blend	N/A	2-4	N/A	N/A	No

3. HAZARDS IDENTIFICATION

OSHA Hazard Communication 29 CFR 1910.1200 Carbon Black, Manganese Compound **4. FIRST AID MEASURES**

EFFECTS OF OVEREXPOSURE					
Eye ContactDirect contact may cause inritation.					
Skin Contact Prolonged contact or repeated exposure may cause minor irritation.					
Inhalation Excess inhalation of mist or vapor may cause dizziness, nausea or irritation	n				
of nasal and respiratory passages.					
Ingestion					
Medical Conditions aggravated by normal exposure: Persons with dematitis should avoid skin contact.					
Target Organs:Skin, eyes, lurgs.					
Primary Routes of entryEyes, inhalation, dennal.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact Flush with large amounts of water until irritation subsides.					
If initation persists, contact a physician.					
Skin Contact:					
thoroughly before reusing.					
Ingestion					
InhalationRemove individual to fresh air.					

5. FIRE FIGHTING MEASURES

	Flash Point	Above 250 F Method used: closed cup
	Explosion Limits	LEL: N/A UEL: N/A
	Extinguishing Media	Foam, carbon dioxide, dry chemical. Water spray may be
		applied to cool exposed closed containers.
		Dense smoke may be generated when burning. Carbon
		Monoxide and Carbon Dioxide generated as combustion products
	Special Fire Fighting Procedures	Self-contained breathing apparatus recommended.
~		

6. ACCIDENTAL RELEASE MEASURES

Procedure when material spilled or released: W ipe up. Dispose of wipes in approved waste containers. If petroleum hydrocarbon is used, provide sufficient vertilation. W aste Disposal Method: Dispose of in accordance with Federal, State and Local regulations.

7. HANDLING AND STORAGE

Handling: Other Precautions: Avoid storage above 90 F. Keep containers closed when not in use. None required.

pH: N/A

240 Grams/liter Method 24

Vapor Pressure: less than 0.04psi

Coefficient of Water/oil Distribution: N/A

Freezing Point ^oF: N/A

Specific Gravity: 1.05 Odor Threshold: N/A

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: Protective Gloves: Respiratory Protection: Use sufficient vertilation. Gloves recommended. None required. Eye Protection: Other Protection: Goggles recommended. None required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Volatile Organic Compounds: (VOCs) 2.10 lbs./gallon Boiling Range °F:> 500 Vapor Density vs. Air: Heavier Density: 8.78 lbs./gallon ASTMD1475 Type of Odor: Oily Appearance: Black viscous paste. Evaporation Rate vs. Butyl Acetate: Slower Percentage Volatile By Weight: 25% ASTMD2369

10. STABILITY AND REACTIVITY

Product Stability: Stable Conditions to Avoid: Strong oxidizing agents Avoid storage above 90 F. Keep containers closed when not in use.

Hazardous Decomposition Products: None. Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Carcinogen Contains no materials that are considered carcinogenic by OSHA or the National Toxicology Program (NIP). The International Agency for Research on Cancer (IARC) lists obalt compounds and carbon black as possible human carcinogens (Class 2B.)

MutagenNo TeratogenNo Reproductive ToxicityNo

12. ECOLOGICAL INFORMATION

This product has not been evaluated, but there is no evidence to suggest it will cause any significant environmental problem.

13. DISPOSAL CONSIDERATIONS

Material Released or spilled: This product is not regulated under the Federal Resource Conservation and Recovery Act (RCRA) as a hazardous waste. State and/or local regulations may apply. Spill should be contained, absorbed with suitable absorbent material and placed in suitable containers for disposal in a licensed facility in accordance with Local, State and Federal laws. Do not discharge into waterways or sewer systems.

14. TRANSPORT INFORMATION- DOT (HM 181) : Not required Shipping Labels: None required

15. REGULATORY INFORMATION

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of Van Son Holland Ink Corporation of America. The data on this sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The hazards covered are believed to be those most likely to occur in the reasonable or ordinary use of these materials. Van Son Holland Ink Corporation of America assumes no legal responsibility for use or reliance on this data.